


PERFECTA L 323 + PEL 323

BOTTOM STAPLING MACHINES







WEIGHT



MECHANICAL &



STAPLE SIZE

Crown 36 mm Legs 15 – 23 mm Wire diameter



CAPACITY



APPLICATION RANGE

Bottom closure of empty cartons made of solid and corrugated cardboard. With the rapidly adjustable carton guide stop you can comfortably adjust the exact stapling position. Insert your folding carton from the side during the stapling process, so that you as the operator can remain in the same ergonomic position.

TECHNICAL DATA

Mechanical or pneumatic stapling device for staples of the series MG® 300; leg length 15 – 23 mm, suitable for solid, single and double-corrugated cardboard. The removable anvil provides a penetrating stapling, as well as an optional blind stapling. The working height in the standard version is 995 mm. For larger quantities we recommend our twin-head version.

ТҮРЕ	L 323	PEL 323
Version	mechanical	pneumatic
Dimensions (W x D x H)	700 x 1000 x 1300 mm	700 x 1000 x 1300 mm
Weight	64 kg	55 kg
Leg length of the staples	15, 20, 23 mm	15, 20, 23 mm
Load capacity: (number of staples)	180	180
Max. carton sizes: (Length x width x height) incl. 1 flap*	100 x 80 x 70* cm	100 x 75 x 85* cm
Air pressure	_	4 – 6 bar
Air consumption per stapling process at 6 bar	-	approx. 4 NL





